



NOTES:

1. MATR'L: 316 SS MAIN BODY PARTS, 18-8 SS FASTENERS, PLASTICS & ELASTOMERS
2. WEIGHT: 32.5 LBS
3. INLET: 2" NPT / 2-1/2" CAMLOCK
4. FLOW RANGE: 25-300 GPM
5. PRESSURE RANGE: 20-300 PSI
6. MINIMUM CYCLE TIME: 6 MINS
7. CLEARANCE: 11.95"

THIS DRAWING IS THE PROPERTY OF GAMAJET CLEANING SYSTEMS, INC. REPRODUCTIONS AND USE OTHER THAN BORROWER'S AGREEMENT IS PROHIBITED. THIS DOCUMENT SHALL NOT BE LENT OR DISPOSED OF DIRECTLY OR INDIRECTLY NOR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IS SPECIFICALLY FURNISHED.

DIMENSIONS ARE IN INCHES
DIMENSIONS INTERPRETED PER
ASME 14.5M-1994
TOLERANCES:
X ±1/16
.XX ±0.010
.XXX ±0.005
ANGLE ±0.5°

DRAWN BY: GES
DRAWN DATE: 13AUG13

APPROVED BY: GES
APPROVED DATE: 13AUG13

SIZE: A SCALE: 1:5 FINISH: SEE NOTE

MATERIAL: SEE NOTE

REVISIONS				
REV	ECN/DESCRIPTION	BY	DATE	APR
1	NEW RELEASE	GES	8/13/13	GES

GAMAJET CLEANING SYSTEMS, INC.
604 JEFFERS CIRCLE
EXTON, PA 19341

DESCRIPTION
105° DIRECTIONAL
GJ-4 CUT-SHEET

DWG. NO.
GJ 4-9000 CUTSHEET



REV 01
SHEET 1/1