



Notes:

- 316 SS, 18-8 Fasteners, Plastics and Elastomers
- Weight = 4.4 Lbs
- Nozzle Sizes: Range from .100" to .200"
- Pressure Range: 50 to 70 PSIG (7 to 70 bar)
- Flow Range: 5 to 6 GPM
- Min. Full Wash Cycle: 3.5 minutes
- Clearance: Designed to fit through a 2" (50mm) bung hole
- Temperature: 180°F (82°C) Max.

UNLESS OTHERWISE SPECIFIED
 * DIMENSIONS ARE IN INCHES
 * DIMENSIONS REFERENCE THEORETICAL SHARP CORNERS
 * FILLET RAD.: 0.015 ±0.005
 * TOLERANCES:
 .XX ±0.01
 .XXX ±0.005
 ANGLE ±0.5°

GAMAJET CLEANING SYSTEMS, INC.
 604 Jeffers Circle
 Exton, PA 19341

NAME
GAMAJET GENTLEJET

EQUIPMENT
 GAMAJET HD-BB

DRAWN BY GES	DRAWN DATE 6/24/2011	REV 02
-----------------	-------------------------	-----------

DWG. NO. GJ HDBB-1000-LP CS	SHEET 1 OF 1
--------------------------------	--------------

MATERIAL:
316 SS

FINISH (UNLESS OTHERWISE SPECIFIED):
32 Ra

SCALE 1:3

THIS DRAWING IS THE PROPERTY OF GAMAJET CLEANING SYSTEMS, INC. REPRODUCTIONS AND USE OTHER THAN BORROWER'S AGREEMENT IS PROHIBITED. THIS DOCUMENT SHALL NOT BE LENT OR DISPOSED OF DIRECTLY OR INDIRECTLY NOR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IS SPECIFICALLY FURNISHED.

REVISIONS TABLE				
DRAWN BY	DATE	REV.	DESCRIPTION	
GES	6/24/11	1	NEW RELEASE	
GES	12/15/11	2	CHANGED DOCUMENT NAME FROM LOW PRESSURE GAMAJET HD-BB	